

## **General Disclaimer**

### **One or more of the Following Statements may affect this Document**

- This document has been reproduced from the best copy furnished by the organizational source. It is being released in the interest of making available as much information as possible.
- This document may contain data, which exceeds the sheet parameters. It was furnished in this condition by the organizational source and is the best copy available.
- This document may contain tone-on-tone or color graphs, charts and/or pictures, which have been reproduced in black and white.
- This document is paginated as submitted by the original source.
- Portions of this document are not fully legible due to the historical nature of some of the material. However, it is the best reproduction available from the original submission.



HUNTSVILLE RESEARCH & ENGINEERING CENTER  
P.O. BOX 1103, HUNTSVILLE, ALABAMA 35807

In reply refer to:  
LMSC-HREC PR F042316  
1 February 1985

National Aeronautics and Space Administration  
George C. Marshall Space Flight Center  
Marshall Space Flight Center, Alabama 35812

Attention: AP29-F

Subject: Contract NAS8-35984, "HPFTP Flow Diverter Analysis," Monthly  
Progress Report

Report Period: January 1985

Gentlemen:

This letter is submitted in accordance with the provisions of Exhibit "A" of the subject contract and describes the direction of effort and accomplishments for the period shown above. This study is being performed by personnel in the Computational Mechanics Section of the Lockheed-Huntsville Research & Engineering Center.

#### Introduction

A computational fluid flow analysis will be conducted on the flow diverter system currently under consideration for the Space Shuttle Main Engine High Pressure Fuel Turbopump (SSME HPFTP). A three-dimensional viscous flow environment will be computed to optimize the geometric configuration and location of the flow diverter system. The analysis will consist of a fully turbulent cold flow calculation using the Navier-Stokes equations and a Baldwin-Lomax turbulence model. The equations will be solved numerically using a finite difference/element procedure. The results of the analysis will provide the steady and unsteady pressure field and thermal environment required to assess the usefulness of the flow diverter system in deflecting the cold flow away from the hot turbine components. A geometry optimization study will be conducted to determine the best diverter shape and location to avoid larger thermal gradients on the rotor/stator components.



Progress Summary

A meeting was held with the NASA-MSFC Contracting Officer's Representative to establish specific items to be accomplished, to set-up a schedule and to initiate the tasks. A final version of this work plan will be presented in next month's report.

Planned Activities

A final version of the work plan will be prepared. Task 1 will be initiated.

Total cumulative costs incurred on Contract NAS8-35984 through January 1985 were zero, insomuch as only preplanning work has been completed. Estimated cost to complete the contract is \$156,955.

Very truly yours,

LOCKHEED MISSILES & SPACE CO., Inc.

  
L.W. Spradley  
Computational Mechanics Group

LWS:pgp

Distribution:

AP29-F, one copy  
AS24D, three copies  
CC01 (L.D. Wofford, Jr.), one copy  
AT01, one copy  
EM13B-11, one copy  
ED31 (G.A. Wilhold), nine copies  
DCASMA (Bham), one copy  
S&TIC (Balt), two copies

WPID:0531C